











SOLARIUM

IRRIGATION

TREADMILL

SAFETY WALL

WALKER

Walker Fencing Sublime for roofs Inside and outside ring including gate

Fencing for a 18-meter roof / Article no. 17-4-30-10018



Our sustainable steel fencing for track roofs and Ifull roof covers, crafted with high-quality steel C-profiles. Each truss section is equipped with 2 fencing sections, which can be filled according to your preference with plastic boards, pressure-treated wood boards, or hardwood planks. Explore the versatility and quality of our fencing options for a stylish and functional addition to the roof.

All steel components are thermally galvanized, and the fencing is supplied with all necessary fastening materials.







SOLARIUM



IRRIGATION





TREADMILL

WALKER







SAFETY WALL

Features

Outside Fencing:

The robust and durable fence for the roofs, with a height of 1.6 meters for optimal safety. The posts between the rafters, securely connected to purlins, are cast in concrete for additional stability. The steel C-profile below, above, and doubled in the middle is suitable for boards up to 32 mm thick, resulting in an extremely solid enclosure. The outer fence also includes a gate of 2x2 meters, with a C-profile below and above suitable for boards up to 32 mm thick. The upper part of the gate is standardly equipped with bars, providing a perfect combination of safety and aesthetics.

Inside Fencing:

With a height of 1.6 meters, our indoor fence provides optimal safety. The posts are cast in concrete for extra stability. The C-profile below, above, and doubled in the middle is suitable for boards up to 32 mm thick, resulting in an extremely solid enclosure.

The indoor fence features a gate of 2x1.6 meters, with a C-profile below, above, and doubled in the middle, suitable for boards of up to 32 mm thick, including 1 heavy-duty beam where the gate is suspended between.

Discover the durability and safety of our indoor and outdoor enclosures for a stylish addition to your canopy.





C

SOLARIUM



IRRIGATION





TREADMILL

LL SAFETY WALL

WALKER

Standard options



Plastic Planks



Impregnated Planks



Hardwood Planks



Fast setting concrete











SOLARIUM

°

IRRIGATION

TREADMILL

SAFETY WALL

WALKER

Specifications

Basic material
Fixings
Thickness
Suited for
Height
Length
Not included
Optional
Other

Steel galvanized included 50 mm Passage and Dome roofs 1,6 meter 2x ca 2 meter Panel filling, Concrete Powder coating Consists of 48 compartments

Contact details

Q-Line Equestrian B.V. Haarbrinksweg 47 7678 RS Geesteren Tel. +31(0)546212361 info@Q-Line.com www.q-line.com