



Q-LINE



SOLARIUM



IRRIGATION



TREADMILL



SAFETY WALL




WALKER

Maxuss Twin 400

Double solarium with LED

Maxuss Twin 400 LED / Article no. 20-5-25-10400




SOLARIUM

IRRIGATION

TREADMILL

SAFETY WALL

WALKER

The solarium, with a beautifully finished body, follows the lines of the horse and consists of 6 main parts for extra warmth. Each muscle group is properly lit by the IR lamps. Due to the heat-resistant plastic, the lamps in plastic holders and by reusing residual heat, a very high efficiency can be achieved. The solarium is finished with rounded edges, which eliminates the risk of injury to your horse. The lamps are placed higher than the bottom surfaces. This minimizes the chance of contact with the warm IR lamps.

Image not found **Stylish Shaped**

Image not found **Lightweight Design**

Image not found **High Heat Output**

Image not found **Heat Resistant plastic**

Image not found **Spray water proof**



Features

Safety:

The Q-line® solarium have been finished with round sides and corners which excludes the chance your horse will get injured. The lamps are placed higher than the holders so that the horse can never come in to direct contact with the lamps.

Durability:

The Q-line® solarium use up to 40% less energy than competitive products and are remarkably environmentally friendly. The heat resistant plastic is insensitive to corrosion and ensure minimal heat loss and a high efficiency. The infrared lights in the Q-line® solarium are designed to be especially heat resistant and can endure great temperatures for extensive periods of time. These lamps can burn up to 5000 hours.

External characteristics:

The Q-line® solarium have a stylish appearance and smooth finishing. All solarium can be used directly and require no further assembly.



SOLARIUM



IRRIGATION



TREADMILL



SAFETY WALL



WALKER

The fans automatically switch on at an internal temperature of 30 degrees C so that no cold air is blown over your horse. 12 built-in spots distributed over the entire bottom surface provide sufficient light during washing and cleaning.

Maintenance:

The Q-line® solaria require little to no maintenance. With our technologically advanced design and the choice of materials we have ensured that corrosion is kept to a minimum.

Quality mark:

All Q-line® solaria conform to the machine code 2006/42/EG and are fit with the CE norm. The Q-line® solaria are certified according to the NEN 3140 and Labor and health directive en hereby conform to all European safety demands



SOLARIUM



IRRIGATION



TREADMILL



SAFETY WALL



WALKER

Configuration & options



Control CB IR AB L 400



Control MT IR AB L 400



Control ET-IR AB, L 400



Electric Lift 170 Extreme Duty



12 RGB LED



Solarium Installation

**SOLARIUM****IRRIGATION****TREADMILL****SAFETY WALL****WALKER**

Specifications

Length	240 cm
Width	249 cm
Drive system	97 cm
Drive system	140 Kg
Basic material	Reinforced heat resisting plastic
Colour	Black / Silver Grey
Number of IR lamps	12x IR 100W, 24x IR 150W, 12x IR 250W
Power supply	3xL+N+PE 400 Volt
Power usage	8220 Watt
Fuse with	C 16 A
Air blower	12 x 90m3, automatic at 30grC
Suspension	4x chians (1 meter) and swing hooks
Suplied as standard	Switch, Power cable 10 mtr including plugs
Quality mark	CE / NEN 3140 / OSH
IP rating	54
Transport weight	2x 80 kg
Transport size	2x 150 x 85x 170 cm
Number of LED lamps	12x 5w 4000K

Contact details

Q-Line Equestrian B.V.

Haarbrinksweg 47

7678 RS Geesteren

Tel. +31(0)546212361

info@Q-Line.com

www.q-line.com