

**SOLARIUM****IRRIGATION****TREADMILL****SAFETY WALL****WALKER**

Solarium control basic

Infrared, fan and LED

Control CB IR AB L 230 / Article no. 21-5-80-10005




SOLARIUM

IRRIGATION

TREADMILL

SAFETY WALL

WALKER

Simple control box for operating the solarium. Supplied ready to plug in, including the necessary cables with plugs and equipped with the following operating elements.

Infrared control; IR

The Infrared lamps can be switched on and off by a manually operated switch.

Fan control; AB

The fans are operated with a 3-position switch with which they can be switched off, automatically or constantly.

LED lighting control; L

The LED lighting is switched with a manually operated switch.

Image not found 230 Volt unknown

Image not found Simple operation

Image not found Including cables



Features

Safety:

The control box is splash-proof and equipped with a lockable main switch.

Appearance:

The control box has a power cord with plug and a cable of approx. 10 m including plug for the solarium.

Maintenance:

Due to the technologically advanced design and the materials used, there is virtually no wear or corrosion, which means that hardly any maintenance is required.

Quality mark:

All control boxes comply with the machine directive 2006 / 42EG and are provided with the CE mark as standard. The boxes are also tested ex works according to the NEN 3140 and OSH directive and therefore meet all European safety requirements.

Control:

The IR lamps are switched with the on / off switch.

The fans can be switched off or on and there is an “automatic” position. In this position, the fans do not switch on until the temperature in the solarium is 30°C.

The LED lighting can be switched on with the appropriate switch.

**SOLARIUM****IRRIGATION****TREADMILL****SAFETY WALL****WALKER**

Specifications

Length	23 cm
Width	19 cm
Drive system	14 cm
Drive system	5 kg
Colour	Grey
Fixings	Included
Cable length	10 meter
Power cord	2,5 meter
Power supply	230 V
Switching capacity	3600 Watt
Basic material	Plastic
IP rating	65
Quality mark	CE / NEN 3140 / OSH
Transport weight	6 kg
Transport size	40x30x30 cm

Contact details

Q-Line Equestrian B.V.

Haarbrinksweg 47

7678 RS Geesteren

Tel. +31(0)546212361

info@Q-Line.com

www.q-line.com