


SOLARIUM

IRRIGATION

TREADMILL

SAFETY WALL

WALKER

Solarium control timer

Infrared, fan and lift

Control MT IR AB EL 230 / Article no. 21-5-80-10010



Simple control box for operating the solarium. Supplied ready to plug in, including the necessary cables with plugs and equipped with the following operating elements.

Infrared control; IR

The Infrared lamps can be switched on and off by a manually timer operated switch.

Fan control; AB

The fans are operated with a 3-position switch with which they can be switched off, automatically or constantly.

Electrical lift operation; EL

The lift is operated with a manual switch that stops the lift when released.

- ✓ 230 Volt
- ✓ Simple operation
- ✓ Including cables



SOLARIUM



IRRIGATION



TREADMILL



SAFETY WALL



WALKER



Features

Safety:

The control box is splash-proof and equipped with a lockable main switch.

Appearance:

The control box has a power cord with plug and a cable of approx. 10 m including plug for the solarium.

Maintenance:

Due to the technologically advanced design and the materials used, there is virtually no wear or corrosion, which means that hardly any maintenance is required.

Quality mark:


All control boxes comply with the machine directive 2006 / 42EG and are provided with the CE mark as standard. The boxes are also tested ex works according to the NEN 3140 and OSH directive and therefore meet all European safety requirements.

Control:

The IR lamps are switched with the mechanical timer switch.

The fans can be switched off or on and there is an "automatic" position. In this position, the fans do not switch on until the temperature in the solarium is 30°C.

The lift for the solarium can be operated with the automatic spring return switch.

**SOLARIUM****IRRIGATION****TREADMILL****SAFETY WALL****WALKER**

Specifications

| | |
|---------------------------|---------------------|
| Length | 23 cm |
| Width | 19 cm |
| Drive system | 14 cm |
| Drive system | 5 Kg |
| Basic material | Plastic |
| Colour | Grey |
| Time | Adjustable 30 min |
| Fixings | Included |
| Cable length | 10 meter |
| Power supply | L+N+PE 230 Volt |
| Switching capacity | 3600 Watt |
| Fuse with | 16 A |
| IP rating | IP 65 |
| Quality mark | CE / NEN 3140 / OSH |

Contact details

Q-Line Equestrian B.V.

Haarbrinksweg 47

7678 RS Geesteren

Tel. +31(0)546212361

info@Q-Line.com

www.q-line.com