

Solarium control electronic timer

Infrared and fan

Control ET-IR AB 230 / Article no. 21-5-80-21110



Advanced control cabinet for operating the solarium, equipped with the specially developed Q-Line timer circuit board. The board features an on-board timer that can be adjusted using a potentiometer. The cabinet is equipped with the following control elements.

The cabinet is equipped with the following control elements.

Infrared control; IR

The Infrared lamps can be switched on and off by a manually operated switch.

Fan control; AB

The fans are operated with a 3-position switch with which they can be switched off, automatically or constantly.

- ✓ Electronic timer
- ✓ Soft start
- ✓ Including cables



SOLARIUM



IRRIGATION



TREADMILL



SAFETY WALL



WALKER



Features

Safety:

The control box is splash-proof and equipped with a lockable main switch.

Appearance:

The control box has a power cord with plug and a cable of approx. 10 m including plug for the solarium.

Maintenance:

Due to the technologically advanced design and the materials used, there is virtually no wear or corrosion, which means that hardly any maintenance is required.

Quality mark:

All control boxes comply with the machine directive 2006 / 42EG and are provided with the CE mark as standard. The boxes are also tested ex works according to the NEN 3140 and OSH directive and therefore meet all European safety requirements.

Control:

With the potentiometer the total time can be set.

The IR lamps are switched with the on / off switch.

The fans can be switched off or on and there is an "automatic" position. In this position, the fans do not switch on until the temperature in the solarium is 30°C.



SOLARIUM



IRRIGATION



TREADMILL



SAFETY WALL



WALKER

Specifications

Length	24 cm
Width	19 cm
Drive system	9 cm
Drive system	8 Kg
Colour	Grey
Time	30 min adjustable
Housing	Plastic
Fixings	Included
Power cord	Included
Cable length	10 meter
Power supply	L+N+PE 230 Volt
Switching capacity	3600 Watt
Fuse with	16 A
IP rating	65
Quality mark	CE / NEN 3140 / OSH
Transport size	42,5 x 32 x 30 cm
Transport weight	9 kg

Contact details

Q-Line Equestrian B.V.

Haarbrinksweg 47

7678 RS Geesteren

Tel. +31(0)546212361

info@Q-Line.com

www.q-line.com