



SOLARIUM



IRRIGATION



TREADMILL



SAFETY WALL



WALKER

Solarium bracket

Telescope support bracket zinc

Telescope support zinc / Article no. 21-3-00-00075




SOLARIUM

IRRIGATION

TREADMILL

SAFETY WALL

WALKER

Telescopic bracket set consisting of tube profile for mounting between 2 walls incl. Mounting material, maximum space between both walls is 4 m.

Image not found **Simple assembly**

Image not found **Very solid**

Image not found **Maximum freedom of movement**



Features

Safety:

The bracket is designed for a total weight of 60 kg.

Appearance:

The bracket consists of 4 tubes that are easy to assemble. All mounting materials are also included for mounting on the wall.

Maintenance:

The tubes are galvanized as standard acc. To. NEN-EN-ISO 1461-99

Quality mark:

All parts comply with the machine directive 2006 / 42EG and are provided with the CE mark as standard and therefore meet all European safety requirements.

**SOLARIUM****IRRIGATION****TREADMILL****SAFETY WALL****WALKER**

Specifications

Length	4 mtr max
Width	1,5 mtr
Thickness	6 cm
Drive system	60 Kg max
Basic material	galvanized as standard acc. To. NEN-EN-ISO 1461-99
Suplied as standard	Comes as a set of 2
Colour	Zinc
Quality mark	CE / OSH
Fixings	Included
Suspension	Between 2 walls
Transport weight	65 kg
Transport size	300x20x10 cm

Contact details

Q-Line Equestrian B.V.

Haarbrinksweg 47

7678 RS Geesteren

Tel. +31(0)546212361

info@Q-Line.com

www.q-line.com