


SOLARIUM



IRRIGATION



TREADMILL



SAFETY WALL



WALKER

## Basic horse walker


15,2 meter 6 horses

15,2 meter 6 horses / Article no. 22-5-05-00616






Q-LINE



SOLARIUM



IRRIGATION



TREADMILL



SAFETY WALL



WALKER

## Horse Walker

Regular movement is an important part of a horse's daily routine. A horse walker offers a safe and controlled way to let horses move calmly and evenly, even on days when riding or turnout is not possible. At Q-Line, you will find reliable horse walkers designed with a focus on comfort, durability and ease of use.

- ✓ Easy to install
- ✓ Electric shock preparation
- ✓ Low maintenance
- ✓ Easy to operate
- ✓ Mesh drift fences

## Practical solution for private stables

This horse walker is ideal for private stables and smaller horse owners who want to provide quiet and structured movement. The walker is easy to operate and efficient in daily use.

The standard control unit includes:

- an internal timer for automatic direction changes
- stepless speed adjustment via a water-resistant regulator

This allows you to create a movement routine without needing constant supervision.

## Benefits of a horse walker

### Regular movement

A walker supports a consistent routine, especially on days when riding or lunging is not possible. The controlled pace provides structure and rhythm.

### Calm, even activity


The repetitive movement offers a predictable and calm moment, which many owners appreciate for young or sensitive horses.


### Variation through speed and direction

Changing direction and adjusting speed adds variation to the session, keeping it clear and balanced.

### Time-saving for the owner

While your horse moves calmly, you can complete other stable tasks — ensuring movement remains part of the day, even when time is limited.


**SOLARIUM**

**IRRIGATION**

**TREADMILL**

**SAFETY WALL**

**WALKER**


## Features

### **Safety:**

The Q-line® horse exercisers are specially designed to be as safe as they can be and are equipped with a direct drive with elastic coupling, lightweight mesh fences and electrical safety settings. All moving parts are protected from contact.

### **Durability:**

By making use of high quality industrial material we can ensure a long lifespan. The technologically advanced design makes the Q-line® horse exerciser rotate smooth- and quietly. The minimal friction put less strain on the driving engine so that little energy is used.

### **External characteristics:**

In the designing Q-line® has strived to create a compact and minimalist appearance. The push fences hang 2 meter high and are 1,97 meter wide and 1,22 high and are around protected with a plastic cover.

### **Maintenance:**


The Q-line® exerciser is a solid construction and requires little maintenance. The technologically advanced design and choice in materials minimize corrosion so that maintenance is barely needed.

### **Quality mark:**

All Q-Line® Horse exercisers conform to the machine code 2006/42/EG and are fit with the CE quality mark. The Q-line® walkers are certifiably approved according to the NEN 3140 and OSH directive en hereby conform to all European safety requirements.

### **Control:**


The control box is equipped with an internally adjustable timer for direction change. The speed is easy to set with the waterproof speed potentiometer.



SOLARIUM



IRRIGATION



TREADMILL



SAFETY WALL



WALKER

## Configuration & options



Basic fencing 15,8 mtr



Lubrication system 12 months




Shock device set Basic 230



Track irrigation Basic



Control box cover



SOLARIUM



IRRIGATION



TREADMILL



SAFETY WALL



WALKER

## Specifications

<b>Diameter</b>	15,24 meter
<b>nr of horses</b>	6
<b>Height</b>	2,26 meter
<b>Speed</b>	12 kmh adjustable
<b>Time</b>	6 minutes turn time
<b>Drive system</b>	Direct drive
<b>Secure</b>	Shear bolt
<b>Drift Fence</b>	Mesh with all-round protection 2x1,5 mtr
<b>Other</b>	Center post on middle frame
<b>Electronic brake</b>	Yes
<b>Power supply</b>	230V, 50Hz
<b>Fuse with</b>	16A Type F
<b>Power usage</b>	1000 Watt
<b>Included</b>	Shock preparation
<b>Basic material</b>	Galvanised steel NEN-EN-ISO 1461-99.
<b>IP rating</b>	54
<b>Supplied as standard</b>	Controlbox WCB 1.1
<b>Cable length</b>	Motor cable 14 meters
<b>Quality mark</b>	CE / NEN 3140 / OSH
<b>Included</b>	Bouwhandleiding
<b>Transport weight</b>	450 Kg
<b>Transport size</b>	1 pallet 120cm x 100cm x 220cm
<b>Fixings</b>	Including

## Contact details

Q-Line Equestrian B.V.

Haarbrinksweg 47

7678 RS Geesteren

Tel. +31(0)546212361

[info@Q-Line.com](mailto:info@Q-Line.com)

[www.q-line.com](http://www.q-line.com)