



SOLARIUM



IRRIGATION



TREADMILL



SAFETY WALL




WALKER

Basic horse walker

15,2 meter 6 horses

15,2 meter 6 horses / Article no. 22-5-05-00616





SOLARIUM



IRRIGATION



TREADMILL



SAFETY WALL



WALKER

Horse Walker

Regular movement is an important part of a horse's daily routine. A horse walker offers a safe and controlled way to let horses move calmly and evenly, even on days when riding or turnout is not possible. At Q-Line, you will find reliable horse walkers designed with a focus on comfort, durability and ease of use.

Practical solution for private stables

This horse walker is ideal for private stables and smaller horse owners who want to provide quiet and structured movement. The walker is easy to operate and efficient in daily use.

The standard control unit includes:

- an internal timer for automatic direction changes
- stepless speed adjustment via a water-resistant regulator

This allows you to create a movement routine without needing constant supervision.

Benefits of a horse walker

Regular movement

A walker supports a consistent routine, especially on days when riding or lunging is not possible. The controlled pace provides structure and rhythm.

Calm, even activity

The repetitive movement offers a predictable and calm moment, which many owners appreciate for young or sensitive horses.

Variation through speed and direction

Changing direction and adjusting speed adds variation to the session, keeping it clear and balanced.

Time-saving for the owner

While your horse moves calmly, you can complete other stable tasks — ensuring movement remains part of the day, even when time is limited.

Image not found Easy to install

Image not found Electric shock preparation

Image not found Low maintenance

Image not found Easy to operate

Image not found Mesh drift fences


SOLARIUM

IRRIGATION

TREADMILL

SAFETY WALL

WALKER


Features

Safety:

The Q-line® horse exercisers are specially designed to be as safe as they can be and are equipped with a direct drive with elastic coupling, lightweight mesh fences and electrical safety settings. All moving parts are protected from contact.

Durability:

By making use of high quality industrial material we can ensure a long lifespan. The technologically advanced design makes the Q-line® horse exerciser rotate smooth- and quietly. The minimal friction put less strain on the driving engine so that little energy is used.

External characteristics:

In the designing Q-line® has strived to create a compact and minimalistic appearance. The push fences hang 2 meter high and are 1,97 meter wide and 1,22 high and are around protected with a plastic cover.

Maintenance:

The Q-line® exerciser is a solid construction and requires little maintenance. The technologically advanced design and choice in materials minimize corrosion so that maintenance is barely needed.


Quality mark:

All Q-Line® Horse exercisers conform to the machine code 2006/42/EG and are fit with the CE quality mark. The Q-line® walkers are certifiably approved according to the NEN 3140 and OSH directive en hereby conform to all European safety requirements.

Control:

The control box is equipped with an internally adjustable timer for direction change.

The speed is easy to set with the waterproof speed potentiometer.

**SOLARIUM****IRRIGATION****TREADMILL****SAFETY WALL****WALKER**

Configuration & options

**Basic fencing 15,8 mtr****Lubrication system 12 months****Shock device set Basic 230****Track irrigation Basic****Control box cover**

**SOLARIUM****IRRIGATION****TREADMILL****SAFETY WALL****WALKER**

Specifications

Diameter	15,24 meter
nr of horses	6
Height	2,26 meter
Speed	12 kmh adjustable
Time	6 minutes turn time
Drive system	Direct drive
Secure	Shear bolt
Drift Fence	Mesh with all-round protection 2x1,5 mtr
Other	Center post on middle frame
Electronic brake	Yes
Power supply	230V, 50Hz
Fuse with	16A Type F
Power usage	1000 Watt
Included	Shock preparation
Basic material	Galvanised steel NEN-EN-ISO 1461-99.
IP rating	54
Suplied as standard	Controlbox WCB 1.1
Cable length	Motor cable 14 meters
Quality mark	CE / NEN 3140 / OSH
Included	Bouwhandleiding
Transport weight	450 Kg
Transport size	1 pallet 120cm x 100cm x 220cm
Fixings	Including

Contact details

Q-Line Equestrian B.V.

Haarbrinksweg 47

7678 RS Geesteren

Tel. +31(0)546212361

info@Q-Line.com

www.q-line.com