











IRRIGATION TREADMILL

EADMILL SAFETY WALL

**Basic XL horse walker** 

# 18 meter 6 horses

18 meter 6 horses / Article no. 22-5-15-00618



This model is very suitable for the private stable with its own horses. With a safe feeling you can work your horses knowing they are getting the right exercise simply but effectively. The standard walk control provides your horse the daily exercise. As standard it is equipped with adjustable timer for direction change and the speed can easily be adjusted with the speedometer.

- elastic coupling
- Electric shock preparation
- Low maintenance
- Easy to operate
- Mesh drift fences

















TREADMILL SAFETY WALL







## **Features**

### Safety:

The Q-line® horse exercisers are specially designed to be as safe as they can be and are equipped with a direct drive with elastic coupling, lightweight mesh fences and electrical safety settings. All moving parts are protected from contact.

#### **Durability:**

By making use of high quality industrial material we can ensure a long lifespan. The technologically advanced design makes the Q-line® horse exerciser rotate smooth- and quietly. The minimal friction put less strain on the driving engine so that little energy is used.

#### **External characteristics:**

In the designing Q-line® has strived to create a compact and minimalistic appearance. The push fences hang 2 meter high and are 1,97 meter wide and 1,22 high and are around protected with a plastic cover.

#### Maintenance:

The Q-line® exerciser is a solid construction and requires little maintenance. The technologically advanced design and choice in materials minimize corrosion so that maintenance is barely needed.

### Quality mark:

All Q-Line® Horse exercisers conform to the machine code 2006/42/EG and are fit with the CE quality mark. The Q-line® solaria are certifiably approved by KEMA according to the NEN 3140 and OSH directive en hereby conform to all European safety requirements.

#### Control:


The control box is equipped with an internally adjustable timer for direction change.

The speed is easy to set with the waterproof speed potentiometer.









TREADMILL





# **Configuration & options**



Basic XL fencing 18,6 mtr



Lubrication system 12 months



Shock device set Basic 230



Track irrigation Basic



Control box cover




**Specifications** 



**SOLARIUM** 



IRRIGATION



**TREADMILL** 



**SAFETY WALL** 



**Diameter** 18 meter

nr of horses 6

**Drive system** Direct drive

Speed12 kmh adjustableTime6 minutes turn time

Drive systemDirect driveSecureElastic coupling

**Drift Fence** Mesh with all-round protection 2x1,5 mtr

Other Center post on middle frame

Electronic brake Yes

Power supply230V, 50HzFuse with16A Type FPower usage1000 WattFixingsIncluding

**Basic material** Galvanised steel NEN-EN-ISO 1461-99.

IP rating 5

Suplied as standardControlbox WCB 1.1Cable lengthMotor cable 14 metersQuality markCE / NEN 3140 / OSHIncludedShock preparation

Transport weight 450Kg

**Transport size** 1 pallet 300cm x 80cm x 150cm

## **Contact details**

Q-Line Equestrian B.V.

Haarbrinksweg 47

7678 RS Geesteren

Tel. +31(0)546212361

info@Q-Line.com

www.q-line.com