


SOLARIUM

IRRIGATION

TREADMILL

SAFETY WALL

WALKER

Control box

Basic walk control box WCB1.1

Walk control box 230V 0,75kW / Article no. 23-4-70-11075



The Basic walk control box is equipped with an internally adjustable timer for direction change. The speed is easy to set with the waterproof speed controller. The on/off button turns the exerciser on and off.

The box is set up for your exerciser. The maximum speed and acceleration and deceleration time depend on the diameter and the number of sections of the exerciser.

- ✓ Reliable
- ✓ Waterproof
- ✓ Easy operation


SOLARIUM

IRRIGATION

TREADMILL

SAFETY WALL

WALKER


Features

Safety:

The Q-line® control boxes are designed to keep your exerciser running as safely as possible. Due to the electronic overload setting, the drive is constantly monitored and the control will switch off in case of overload.

Durability:

By using high-quality industrial parts, we can guarantee a very long lifespan. Thanks to a technologically advanced design and the right settings, the exerciser runs almost silently.

Appearance:

The control box is designed from the user's point of view, simple operating elements that are easily accessible.

Maintenance:

The materials chosen are durable and corrosion-resistant, which means that maintenance is practically not required.

Approvals:

All control cabinets comply with the machine directive 2006/42EG and are standard equipped with the CE quality mark. The Q-line® exercisers are also factory tested according to the NEN 3140 and ARBO directive and therefore meet all European safety requirements.



SOLARIUM



IRRIGATION



TREADMILL



SAFETY WALL



WALKER

Configuration & options



Shock control



Control box heating



Control box cover

**SOLARIUM****IRRIGATION****TREADMILL****SAFETY WALL****WALKER**

Specifications

Housing	Steel coated
Basic material	Steel
Time	Direction change adjustable
Speed	Adjustable
Connection	4 pin plug
Secure	Overload
Electronic brake	Adjustable
Colour	RAL 7035
Power supply	1 fase 200-240V 50/60Hz
Suited for	3x230V / 0,75Kw
Ampere	11
Fuse with	16A Type C
Switching capacity	0,75 Kw 4,3A
Power usage	1,65 KVA
Power cord	2mtr 230V 3x1,5mm2
Weight	7 kg
Height	30 cm
Width	25 cm
Thickness	16 cm
IP rating	IP 66
Quality mark	CE
Fixings	Included
Transport weight	8 kg
Transport size	43 x 32 x 30 cm

Contact details

Q-Line Equestrian B.V.

Haarbrinksweg 47

7678 RS Geesteren

Tel. +31(0)546212361

info@Q-Line.com

www.q-line.com