







TREADMILL





Control box

Programmable walk/trot control box WCB 3.1

Programmable box 230V- 0,75KW / Article no. 23-4-70-30075



The Sublime advanced walk/trot control box is equipped with a programmable control. Because each step is programmable, you can combine endlessly. It is very easy to operate using the numeric keypad and navigation arrows. Train your horses well and easily.

The control box is set up for your exerciser. The maximum speed and acceleration and deceleration time depend on the diameter and the number of sections of the exerciser.

Various messages are displayed on the illuminated screen, such as when the exerciser needs to be lubricated again.

- Reliable
- Waterproof
- Easy operation









TREADMILL











Features

Safety:

The Q-line® control boxes are designed to keep your exerciser running as safely as possible. Due to the electronic overload setting, the drive is constantly monitored and the control will switch off in case of overload.

Durability:

By using high-quality industrial parts, we can guarantee a very long lifespan. Thanks to a technologically advanced design and the right settings, the exerciser runs almost silently.

Appearance:

The control box is designed from the user's point of view, simple operating elements that are easily accessible.

Maintenance

The materials chosen are durable and corrosion-resistant, which means that maintenance is practically not required.


Approvals:

All control cabinets comply with the machine directive 2006/42EG and are standard equipped with the CE quality mark. The Q-line® exercisers are also factory tested according to the NEN 3140 and ARBO directive and therefore meet all European safety requirements.









TREADMILL





Configuration & options







Shock control


Control box heating

Control box cover













WALKER

SOLARIUM

IRRIGATION

TREADMILL

SAFETY WALL

Specifications

Housing Basic material

Time Speed Connection Secure

Electronic brake

Colour

Power supply

Suited for Ampere

Fuse with

Switching capacity

Power usage Power cord

Weight Height Width

Thickness
IP rating
Quality mark

Fixings

Transport weight

Transport size

Fiberglass
Fiberglass
Programmable
Programmable
4 pin plug
Overload
Adjustable

RAL 7035

1 fase 200-240V 50/60Hz

3x230V / 0,75Kw

11

16A Type C 0,75 Kw 4,3A 1,65 KVA

2mtr 230V 3x1,5mm2

9 kg 43 cm 33 cm 20 cm IP 66 CE Included

10 kg

50 x 50 x 27 cm

Contact details

Q-Line Equestrian B.V.

Haarbrinksweg 47

7678 RS Geesteren

Tel. +31(0)546212361

info@Q-Line.com

www.q-line.com