Q-LINE

SOLARIUM IRRIGATION TREADMILL SAFETY WALL WALKER

Lubrication Solutions

Sublime automatic lubrication system

USD Lubrication System Sublime / Article no. 23-4-05-00100



Q-LINE.COM

Q-LINE

SOLARIUM IRRIGATION TREADMILL SAFETY WALL WALKER

Proper lubrication of the rotating parts is essential to reduce failure and increase exerciser life.

An automatic lubrication system intended for automating and centralizing grease lubrication is a solution. The system consists of a hose with couplings and a grease cartridge.

The grease cartridge works without a battery and is adjustable between 1 and 12 months. Depending on the use of the mill, you set the period.

This lubrication system is extremely suitable for exercisers that are mounted in the ridge of the roof. The unit is hung next to the control box and connected by the supplied hose to the ring bearing.

- Replaceable grease cartridges
- Low installation costs
- Compact and reliable
- 12 months maintenance free
- Temperature range -15° C to +60°C
- Multifunctional, indoor and outdoor
- No chemical waste







Features


Q-LINE.COM

Configuration & options



USD service pack

Q-LINE


SOLARIUM


IRRIGATION


TREADMILL


SAFETY WALL


WALKER

Specifications

Connection	3/8" BU BSPT
Drive system	Battery
Basic material	Plastic
Required working pressure	30-60 bar
Fixings	Mounting bracket
Suited for	Slewing ring
Weight	2 kg
Included	20 mtr hose
IP rating	54
Other	250CC
Time	1,2,3,6,12 months
Transport weight	3 kg
Transport size	38 x 28 x 17 cm

Contact details

Q-Line Equestrian B.V.

Haarbrinksweg 47

7678 RS Geesteren

Tel. +31(0)546212361

info@Q-Line.com

www.q-line.com

Q-LINE.COM