




SOLARIUM



IRRIGATION



TREADMILL



SAFETY WALL



WALKER

Roller treadmill

Treadmill for horses

Roller treadmill / Article no. 27-5-00-10230




SOLARIUM

IRRIGATION

TREADMILL

SAFETY WALL

WALKER

Revolutionize Equine Training with Our Advanced Roller Treadmill

Experience the innovative Roller Treadmill, uniquely designed with micro rollers to enhance your horse's hoof blood circulation. This treadmill stands out from traditional models with its friction-reducing mechanism, ensuring no heat transfer to the horse's hooves, thus promoting a safer and more comfortable exercise environment.

Key Features:

Enhanced Durability:

The reduced friction not only ensures a cooler workout experience but also significantly extends the life of the treadmill's rubber band.

Safety and Control:

Equipped with advanced start-up and brake electronics, an electronic emergency stop unit, and a drum-drive with a mechanical brake for ultimate control and safety.

Slip-resistant Access:

Includes two ramps featuring an anti-slip mat, making it easier and safer for horses to mount and dismount.

Security and Visibility:

Enhanced with two high-stability side walls, crafted from transparent, unbreakable carbonate plates, offering clear visibility and added security.

Robust Construction:

All steel parts are galvanized and/or powder-coated, providing long-lasting protection and durability.

The roller treadmill is not only a tool for fitness but also an essential component in rehabilitation and targeted muscle training. Its design prioritizes horse safety, making it an ideal choice for various equestrian disciplines. The positive impact of treadmill training on a horse's endurance, muscle build-up in the fore and hindquarters is well-recognized across the equestrian sports community.

Choose our Roller Treadmill for a superior, controlled training experience, built to the highest standards with your horse's wellbeing in mind.

- ✓ Energy efficient
- ✓ 230V / 2,2Kw
- ✓ IR trip fence
- ✓ User friendly
- ✓ Easy to install
- ✓ Smooth side walls
- ✓ Various safety features
- ✓ Low maintenance





SOLARIUM



IRRIGATION



TREADMILL



SAFETY WALL



WALKER

Features

Safety:

The Q-line® treadmills can only move in height when the motor is on. This prevents the horse from walking uncontrolled and thus falling. If a malfunction occurs in the treadmill, the height adjustment is automatically reset and returns to the horizontal position.

Durability:

By using high-quality industrial parts, we can guarantee a very long lifespan. Thanks to a technologically advanced design, the belt glides almost silently and very lightly, making the Q-line® treadmills particularly energy-efficient.

Appearance:

The treadmill trainer is a well thought-out technological solution and is characterized by the flexible bottom and solid construction. In which a running quality is obtained that is comparable to a natural soil.

Lifespan:


Q-line® treadmills are made of high-quality material. The drum motors in the treadmills are water and dust proof and are therefore considerably less sensitive to malfunctions. Thanks to a completely galvanized construction, the Q-line® treadmills can also be used outdoors.

Maintenance:

The treadmills require very little maintenance. Due to the technologically advanced design and the materials used, there is virtually no wear or corrosion, which minimizes maintenance.

Quality mark:


All treadmills comply with the machine directive 2006 / 42EG and are provided with the CE mark as standard. The Q-line® mills are also certified ex works according to the NEN 3140 and ARBO directive and therefore meet all European safety requirements.



SOLARIUM



IRRIGATION



TREADMILL



SAFETY WALL



WALKER

Standard options



Manual incline



Programmable incline

**SOLARIUM****IRRIGATION****TREADMILL****SAFETY WALL****WALKER**

Specifications

Drive system	Drum motor
nr of horses	1
Suited for	Horses up to 800 kg
Secure	Infra red fence / Mechanical break
Speed	10 km / h manually with potentiometer
Other	Side wall: polycarbonate
Suplied as standard	Ramp at the front and rear
Optional	Height adjustment
Basic material	Steel
Colour	Zinc or powdercoating RAL xxxx
Length	Walkway 342 cm / total 650 cm
Height	214 cm
Width	135 cm
Thickness	31 cm
IP rating	55
Quality mark	CE
Power cord	230/240V L-N-PE
Power supply	230/240V 50/60 Hz
Power usage	4KVA
Ampere	21
Fuse with	25A
Transport weight	1750 kg
Transport size	380 x 140 x 220 cm

Contact details

Q-Line Equestrian B.V.

Haarbrinksweg 47

7678 RS Geesteren

Tel. +31(0)546212361

info@Q-Line.com

www.q-line.com