



SOLARIUM



IRRIGATION



TREADMILL



SAFETY WALL



WALKER

Pop up irrigation

Automatic operation

Pop up Sublime 20x40 / Article no. 26-5-10-02040




SOLARIUM

IRRIGATION

TREADMILL

SAFETY WALL

WALKER

Dust development is a well-known issue in riding arenas. Low humidity and intensive use of the ground quickly lead to swirling dust and sand, creating an unstable surface. Training under these conditions is unpleasant and unhealthy for both the horse and the rider.

A regularly irrigated riding arena significantly prolongs its lifespan and provides a better riding surface/track. Q-Line® utilizes special sprinklers in its systems, evenly moistening the riding surface through proper misting. Your riding arena will be durable, dust-free, and smooth with a Q-Line irrigation system.

The Sublime pop-up irrigation system comprises a complete setup operated by a programmable rain computer. Upon purchase, all necessary components for installing this irrigation system are included: hoses, connectors, clamps, Teflon tape, adhesive, nozzles, and 24V electric valves. Additionally, a clear 3D manual is provided, illustrating how the parts should be assembled. You can easily connect your own pump to the system using the supplied 1" adapter.

Image not found **High quality nozzles**

Image not found **Extremely robust**

Image not found **Easy operation**

Image not found **Nozzles fully adjustable 50-360 degrees**


Image not found **Improved waste water tolerance**



Features

Permanently installed pop-up sprinklers are typically positioned alongside the track. Optimal placement ensures even irrigation across the surface. These sprinklers are controlled by a specialized system.


The riding arena is sprayed multiple times based on the number of electric valves, considering water supply and pump capacity. The operation is entirely programmable.



SOLARIUM



IRRIGATION



TREADMILL



SAFETY WALL



WALKER

Configuration & options



Pump set Sublime

**SOLARIUM****IRRIGATION****TREADMILL****SAFETY WALL****WALKER**

Specifications

Width	20 mtr
Length	40 mtr
Nozzles	8
Electric valve	4
Valve voltage	24 V
Required working pressure	4,5 bar
Required liters	3500 l/h
Power supply	230 V
Included	Irrigation computer
Transport size	120x80x150 cm
Transport weight	100 kg
Not included	Pump

Contact details

Q-Line Equestrian B.V.

Haarbrinksweg 47

7678 RS Geesteren

Tel. +31(0)546212361

info@Q-Line.com

www.q-line.com