



Q-LINE



SOLARIUM



IRRIGATION



TREADMILL



SAFETY WALL



WALKER

Irrigation pumps

Self-priming pump set

Pump set Sublime / Article no. 26-5-60-00006




SOLARIUM

IRRIGATION

TREADMILL

SAFETY WALL

WALKER

Discover our powerful self-priming pump, perfectly suited for sublime pop-up irrigation systems 20x40 and 20x60. This pump comes with a power cord, on/off switch, motor protection relay, and pump control relay - all integrated into one enclosure. Complete with a 7-meter long suction hose with spring-loaded non-return valve and a 5-meter delivery pipe, including a pressure relief valve.

Our self-priming pump effortlessly draws water from any source. With a maximum suction depth of 8 meters, this pump can lift various types of water, making it ideal for diverse applications.

This pump is positioned above the water, ensuring the motor does not come into direct contact with the water. The motor support is made of durable aluminum, and the impeller and diffuser are crafted from high-quality technopolymer. Stainless steel retaining rings provide additional strength, and the mechanical seal consists of graphite/ceramic for optimal performance. The motor shaft is made of stainless steel AISI 304. Moreover, the pump is equipped with a built-in thermoamperometric protection and a permanently connected capacitor in the single-phase motor version.

Please note: this pump cannot be connected to an outdoor faucet due to insufficient water supply for optimal operation.

Interested in learning more about our self-priming pump or looking for a reliable solution for your irrigation needs? Feel free to contact us. Our pump is specially designed for basic pop-up irrigation systems, offering powerful performance for every situation. Discover the benefits of our pump today!

Image not found **Low noise**

Image not found **High operational reliability**

Image not found **Resistant to rust and limescale**

Image not found **Ready to use**




Features

Motor support made of die-cast aluminum, end plate seal made of steel AISI 304.

Mechanical seal made of graphite/ceramic.

Rotor shaft made of steel AISI 304. Impellers, housing, and diffuser made of technopolymer.

Wearing rings made of stainless steel.



SOLARIUM



IRRIGATION



TREADMILL



SAFETY WALL



WALKER

Motor protection class: IP 44.

Terminal box protection class: IP 55.

Insulation class: F.

Pumped liquid: clean, free from solid or abrasive components, non-viscous, chemically neutral, closely resembling water in its characteristics.

Temperature range of the pumped liquid: from 0°C to +35°C.

Euroinox self-priming design.

Maximum operating pressure: 8 bar.

**SOLARIUM****IRRIGATION****TREADMILL****SAFETY WALL****WALKER**

Specifications

Suited for	26-5-10-02040 / 26-5-10-02060
Connection	1"
Required liters	0,6 - 7,2 m3/h
Required working pressure	5,7 - 1,65 bar
Housing	pump housing stainless
Length	Pump 46 cm
Width	Pump 17,5 cm
Height	Pump 21 cm
Weight	Pump 15,1 kg
Included	Suction hose 7 m incl. spring-loaded check valve
Other	5 mtr press pipe 32mm PVC and a pressure relief valve.
Cable length	5 mtr
Quality mark	CE
Colour	Green
Supplied as standard	Isolator switch
Secure	Motor protection relay
Power supply	230 V
Power cord	230 V L+N+PE
Ampere	6,3 A
Power usage	1,4 kW
IP rating	IP44 (IP55 on the connection box)
Transport weight	20 kg
Transport size	500x25x25 cm

Contact details

Q-Line Equestrian B.V.

Haarbrinksweg 47

7678 RS Geesteren

Tel. +31(0)546212361

info@Q-Line.com

www.q-line.com