

**SOLARIUM****IRRIGATION****TREADMILL****SAFETY WALL****WALKER**

Solarium control electronic timer

Infrared, fan and LED

Control ET-IR AB, L 230 / Article no. 21-5-80-21115





SOLARIUM



IRRIGATION



TREADMILL



SAFETY WALL



WALKER

Advanced box for operating the solarium, equipped with the specially developed Q-line soft-start circuit board (QSP) for solariums. The QSP ensures that the lamps of the solarium switch on slowly and dim slowly, due to this applied technology the solarium has a lower inrush current. The PCB is also equipped with an on-board timer which can be set by means of a potentiometer.

The cabinet is equipped with the following operating elements.

Infrared control; IR

The Infrared lamps can be switched on and off by a manually operated switch.

Fan control; AB

The fans are operated with a 3-position switch with which they can be switched off, automatically or constantly.

LED lighting control; L

The LED lighting is switched with a manually operated switch.

- ✓ Electronic timer
- ✓ Soft start
- ✓ Including cables



Features



SOLARIUM



IRRIGATION



TREADMILL



SAFETY WALL



WALKER

Safety:

The control box is splash-proof and equipped with a lockable main switch.

Appearance:

The control box has a power cord with plug and a cable of approx. 10 m including plug for the solarium.

Maintenance:

Due to the technologically advanced design and the materials used, there is virtually no wear or corrosion, which means that hardly any maintenance is required.

Quality mark:

All control boxes comply with the machine directive 2006 / 42EG and are provided with the CE mark as standard. The boxes are also tested ex works according to the NEN 3140 and OSH directive and therefore meet all European safety requirements.

Control:

With the potentiometer the total time can be set.

The IR lamps are switched with the on / off switch.

The fans can be switched off or on and there is an “automatic” position. In this position, the fans do not switch on until the temperature in the solarium is 30°C.

The LED lighting can be switched on with the dedicated switch.

**SOLARIUM****IRRIGATION****TREADMILL****SAFETY WALL****WALKER**

Specifications

Length	24 cm
Width	19 cm
Drive system	9 cm
Drive system	8 Kg
Colour	Grey
Time	30 min adjustable
Housing	Plastic
Fixings	Included
Power cord	Included
Cable length	10 meter
Power supply	L+N+PE 230 Volt
Switching capacity	3600 Watt
Fuse with	16 A
IP rating	65
Quality mark	CE / NEN 3140 / OSH
Transport size	42,5 x 32 x 30 cm
Transport weight	9 kg

Contact details

Q-Line Equestrian B.V.

Haarbrinksweg 47

7678 RS Geesteren

Tel. +31(0)546212361

info@Q-Line.com

www.q-line.com